



## ATEX Certificated Explosion Proof Cameras and Housings



Contact us at: [info@securitell-int.com](mailto:info@securitell-int.com) Tel: +27 82 556 6565 Skype: sam.onskype




Photo	Model	Resolution	Lens	EX level	Features
	KX-EX707PW	<b>Housing only without camera inside</b>		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion-proof anti-corrosion, waterproof IR distance: 50-100m inside size: Φ100*300mm window size: Φ65mm Suitable for AC220 power 2*G3/4" interface for wire can assemble box camera, all-in one camera
	KX-EX707PWE	<b>housing only without camera inside</b>		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof Explosion-proof, anti-corrosion, waterproof IR distance: 50-100m inside size: Φ100*290mm window size: Φ65mm Suitable for AC220 power 2*G3/4" interface for wire can assemble box camera, all-in one camera
	KX-EX600PW	<b>housing only without camera inside</b>		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof Explosion-proof, anti-corrosion, waterproof inside size: Φ100*300mm window size: Φ65mm Suitable for AC220 power 2*G3/4" interface for wire can assemble box camera, all-in one camera
	KX-EX601PW	<b>housing only without camera inside</b>		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof Explosion-proof, anti-corrosion, waterproof inside size: Φ100*290mm window size: Φ65mm Suitable for AC220 power 2*G3/4" interface for wire can assemble box camera, all-in one camera
	KX-EX600PWL	<b>housing only without camera inside</b>		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Aluminum, apply to slight corrosive environment. B-B-level Explosion proof Explosion-proof, anti-corrosion, waterproof inside size: Φ105*240mm window size: Φ80mm optional for AC220 power 2*20*1.5mm interface for wire can assemble box camera, all-in one camera
	KX-EX600PWK	<b>housing only without camera inside</b>		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof Explosion-proof, anti-corrosion, waterproof inside size: Φ100*290mm window size: Φ65mm optional for DC12/ AC220 power 2*20*1.5mm interface for wire <b>built-in heater &amp; fan suitable for -45°C→+100°C. Peltier effect: Automatic cooling&gt;40°C.&lt;5°C.self-heating</b> can assemble box camera, all-in one camera
	KX-EX600PWY	<b>housing only without camera inside</b>		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof Explosion-proof, anti-corrosion, waterproof inside size: Φ100*290mm window size: Φ65mm optional for DC/ AC220 power 2*G3/4" interface for wire built-in smart windshield wiper can assemble box camera, all-in one camera

	KX-EX01PWFS	housing only without camera inside	double-layer structure, water & wind cold	double-layer structure, water & wind cold quartz glass window inside size: Φ100*300mm window size: Φ75mm can assemble box camera, all-in one camera 200 degree high temperature
	KX-EX01PWN	housing only without camera inside	Special engineering plastics	Special engineering plastics, Strong anti-corrosion inside size: Φ102*260mm window size: Φ80mm can assemble box camera, all-in one camera

1. Default price 304 stainless steel. Optional material: 316 Extra, 316L Extra


2. KX-EX707PW, KX-EX707PWE, IR distance 50-100m. if you need 100m IR, Extra

3. all models is default is DC 12V. Optional AC 220V Extra

Photo	Model	Resolution	Lens	EX level	Features
	KX-EX1000ZPPS	housing only without camera inside		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof Explosion-proof, anti-corrosion, waterproof IR distance: 100M horizontal 360°, Vertical : ±90°, Horizontal/Vertical Rotate speed 0.1°/s~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000ZPPY	housing only without camera inside		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion-proof, anti-corrosion, waterproof IR distance: 100M (Laser IR) horizontal 360°, Vertical : ±90°, Horizontal Rotate speed 9°/s, Vertical Rotate speed 6°/s Auto-Iris, Auto-Focus, Support SD card 256preset, Support ONVIF, support HIKVISION, DAHUA AC22V/24V optional
	KX-EX1000PPS	housing only without camera inside		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion-proof, anti-corrosion, waterproof horizontal 360°, Vertical : ±90°, Rotate speed 0.1°/s~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V

1. 316 Extra, 316L Extra

2. KX-EX1000ZPPY Series can add windshield wiper

Photo	Model	Resolution	Lens	EX level	Features
	KX-EX2000PSY	housing only without camera inside		ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	6" inch, 304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion-proof, anti-corrosion, waterproof horizontal 360°, Vertical : -5°-90° (AUTO FLIP) Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA SDK, ONVIF CG PSIA GB/T28181 ETC. AC24V

1. Optional material: 316 Extra, 316L Extra

**EXPLOSION-PROOF IR BULLET CAMERA**

Photo	Model	Resolution	Lens	EX level	Features
	KX-EX700PWB13	1.3 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional) apply to strong corrosive environment. C-level Explosion proof Explosion-proof, anti-corrosion, waterproof IR distance: 20-100m
	KX-EX700PWB2	2.0 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	lens: 4/6/8/12/16/25mm for optional Support ONVIF, support HIKVISION, DAHUA DC12V/AC220V for optional
	KX-EX700PWB3	3 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Built-in fan
	KX-EX700PWD13	1.3 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof
	KX-EX700PWD2	2.0 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion-proof, anti-corrosion, waterproof IR distance: 20-100m
	KX-EX700PWD3	3 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	lens: 4/6/8/12/16/25mm for optional Support ONVIF, support HIKVISION, DAHUA DC12V/AC220V for optional
	KX-EX700PWL13	1.3 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Aluminum, apply to slight corrosive environment. B-level Explosion proof
	KX-EX700PWL2	2.0 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion-proof, anti-corrosion, waterproof IR distance: 20-100m
	KX-EX700PWL3	3 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	lens: 4/6/8/12/16/25mm for optional Support ONVIF, support HIKVISION, DAHUA DC12V/AC220V for optional
	KX-EX701PWC13	1.3 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof
	KX-EX701PWC2	2.0 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion-proof, anti-corrosion, waterproof IR distance: 10-30m lens: 4/6mm for optional
	KX-EX707PWJ13	1.3 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof
	KX-EX707PWJ2	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion-proof, anti-corrosion, waterproof IR distance: 50/100m (optional)
	KX-EX707PWJ3	3 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	lens: 2.8-12mm Support ONVIF, support HIKVISION, DAHUA DC12V/AC220V for optional
	KX-EX707PWJ118	1.3 Megapixels	18X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof
	KX-EX707PWJ218	2.0 Megapixels	18X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion-proof, anti-corrosion, waterproof IR distance: 100M (Laser IR) lens: 4.7-84.6mm (18X) Auto-Iris, Auto-Focus, Support SD card Support ONVIF, support HIKVISION, DAHUA DC12V/AC220V for optional
	KX-EX707PWE13	1.3 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof
	KX-EX707PWE2	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion-proof, anti-corrosion, waterproof IR distance: 50/100m (optional)
	KX-EX707PWE3	3 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	lens: 2.8-12mm Support ONVIF, support HIKVISION, DAHUA DC12V/AC220V for optional
	KX-EX707PWE118	1.3 Megapixels	18X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof
	KX-EX707PWE218	2.0 Megapixels	18X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion-proof, anti-corrosion, waterproof IR distance: 100M (Laser IR) lens: 4.7-84.6mm (18X) Auto-Iris, Auto-Focus, Support SD card Support ONVIF, support HIKVISION, DAHUA DC12V/AC220V for optional

1. Optional function: AC220/POE, Audio/Alarm, Wide dynamic, Ultra low lux

2. Optional material: 316 Extra, 316L Extra

3. Optional Resolution: 4MP, 5MP, 20x, 30x for zoom camera

**EXPLOSION-PROOF PTZ CAMERA**

Photo	Model	Resolution	Zoom Ratio	EX level	Features
	KX-EX1000ZPPS118	1.3 Megapixels	18X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof
	KX-EX1000ZPPS120	1.3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion--corrosion, waterproof IR distance: 100M horizontal 360°, Vertical : ±90°, Horizontal/Vertical Rotate speed 0.1°/s~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper
	KX-EX1000ZPPS130	1.3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000ZPPS218	2.0 Megapixels	18X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof
	KX-EX1000ZPPS220	2.0 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion--corrosion, waterproof IR distance: 100M horizontal 360°, Vertical : ±90°, Horizontal/Vertical Rotate speed 0.1°/s~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper
	KX-EX1000ZPPS230	2.0 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000ZPPS320	3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof
	KX-EX1000ZPPS330	3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion--corrosion, waterproof IR distance: 100M horizontal 360°, Vertical : ±90°, Horizontal/Vertical Rotate speed 0.1°/s~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000ZPPY118	1.3 Megapixels	18X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof
	KX-EX1000ZPPY120	1.3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion--corrosion, waterproof IR distance: 100M (Laser IR) horizontal 360°, Vertical : ±90°, Horizontal Rotate speed 9°/s, Vertical Rotate speed 6°/s Auto-Iris, Auto- Focus, Support SD card 300preset, Support ONVIF, support HIKVISION, DAHUA AC22V/24V optional
	KX-EX1000ZPPY130	1.3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	
	KX-EX1000ZPPY218	2.0 Megapixels	18X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof
	KX-EX1000ZPPY220	2.0 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion--corrosion, waterproof IR distance: 100M (Laser IR) horizontal 360°, Vertical : ±90°, Horizontal Rotate speed 9°/s, Vertical Rotate speed 6°/s Auto-Iris, Auto- Focus, Support SD card 256preset, Support ONVIF, support HIKVISION, DAHUA AC22V/24V optional
	KX-EX1000ZPPY230	2.0 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	
	KX-EX1000ZPPY320	3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof
	KX-EX1000ZPPY330	3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion--corrosion, waterproof IR distance: 100M (Laser IR) horizontal 360°, Vertical : ±90°, Horizontal Rotate speed 9°/s, Vertical Rotate speed 6°/s Auto-Iris, Auto- Focus, Support SD card 256preset, Support ONVIF, support HIKVISION, DAHUA AC22V/24V optional



	KX-EX1000PPS118	1.3 Megapixels	18X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof
	KX-EX1000PPS120	1.3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion--corrosion, waterproof horizontal 360°, Vertical : ±90°, Rotate speed0.1° /S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper
	KX-EX1000PPS130	1.3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Support ONVIF; support HIKVISION, DAHUA AC85V-260V
	KX-EX1000PPS218	2.0 Megapixels	18X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof
	KX-EX1000PPS220	2.0 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Explosion-proof, anti-corrosion, waterproof horizontal 360°, Vertical : ±90°, Rotate speed0.1° /S~40°/s Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper
	KX-EX1000PPS230	2.0 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Support ONVIF, support HIKVISION, DAHUA AC85V-260V
	KX-EX1000PPS320	3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion-proof, anti-corrosion, waterproof horizontal 360°, Vertical : ±90°, Rotate speed0.1° /S~40°/s
	KX-EX1000PPS330	3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF; support HIKVISION, DAHUA AC85V-260V

1. Optional 4K, Audio/Alarm, Ultra low lux, 316 Extra, 316L Extra

2. KX-EX1000ZPPY Series can add windshield wiper

### EXPLOSION-PROOF SPEED DOME CAMERA

Photo	Model	Resolution	Zoom Ratio	EX level	Features
	KX-EX2000PSY120	1.3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	6" inch, 304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion--corrosion, waterproof horizontal 360°, Vertical : -5°-90° (AUTO FLIP)
	KX-EX2000PSY130	1.3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA SDK、ONVIF、CGI、PSIA、GB/T28181 ETC. AC24V
	KX-EX2000PSY220	2.0 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	6" inch, 304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion--corrosion, waterproof horizontal 360°, Vertical : -5°-90° (AUTO FLIP)
	KX-EX2000PSY230	2.0 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA SDK、ONVIF、CGI、PSIA、GB/T28181 ETC. AC24V
	KX-EX2000PSY320	3 Megapixels	20X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	6" inch, 304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion--corrosion, waterproof horizontal 360°, Vertical : -5°-90° (AUTO FLIP)
	KX-EX2000PSY330	3 Megapixels	30X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Auto-Iris, Auto-Focus, Support SD card 300preset, smart windshield wiper Support ONVIF, support HIKVISION, DAHUA SDK、ONVIF、CGI、PSIA、GB/T28181 ETC. AC24V

	KX-EX2001PSY110	1.3 Megapixels	10X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	4" inch, 304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion--corrosion, waterproof horizontal 360°, Vertical : 180° (AUTO FLIP) Auto-Iris, Auto-Focus, Support SD card preset Support ONVIF, support HIKVISION, DAHUA DC12V
	KX-EX2001PSY210	2.0 Megapixels	10X	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	
	KX-EX2000PSB13	1.3 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion--corrosion, waterproof IR distance: 20-100m lens: 4/6/8mm for optional Support ONVIF, support HIKVISION, DAHUA
	KX-EX2000PSB20	2.0 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	
	KX-EX2000PSB30	3.0 Megapixels	Fixed	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	

1. Optional function: POE(6 inch only), Audio/Alarm

2. Optional material: 316 Extra, 316L Extra






### EXPLOSION-PROOF BULLET CAMERA (WITHOUT IR)

Photo	Model	Resolution	Zoom Ratio	EX level	Features
	KX-EX600PWA13	1.3 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion--corrosion, waterproof lens: 2.8-12mm Support ONVIF; support HIKVISION, DAHUA DC12V/AC220 Optional
	KX-EX600PWA20	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	
	KX-EX600PWA118	1.3 Megapixels	18x	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion--corrosion, waterproof lens: 4.7-84.6mm, 18x Auto-Iris, Auto-focus, SD card Support ONVIF; support HIKVISION, DAHUA DC12V/AC220 Optional
	KX-EX600PWA218	2.0 Megapixels	18x	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	
	KX-EX601PWA13	1.3 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof Explosion--corrosion, waterproof lens: 2.8-12mm Support ONVIF; support HIKVISION, DAHUA DC12V/AC220 Optional
	KX-EX601PWA20	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	
	KX-EX601PWA118	1.3 Megapixels	18x	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof Explosion--corrosion, waterproof lens: 4.7-84.6mm, 18x Auto-Iris, Auto-focus, SD card Support ONVIF; support HIKVISION, DAHUA DC12V/AC220 Optional
	KX-EX601PWA218	2.0 Megapixels	18x	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	
	KX-EX600PWK13	1.3 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof Explosion--corrosion, waterproof m lens: 2.8-12mm built-in heater & fan suitable for -45°C+100°C Support ONVIF; support HIKVISION, DAHUA DC12V/AC220 Optional
	KX-EX600PWK20	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	
	KX-EX600PWY13	1.3 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. C-level Explosion proof Explosion--corrosion, waterproof m lens: 2.8-12mm built-in smart windshield wiper Support ONVIF; support HIKVISION, DAHUA DC12V/AC220 Optional
	KX-EX600PWY20	2.0 Megapixels	2.8-12mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	

1. Optional function: AC220/POE, Audio/Alarm, Wide dynamic, Ultra low lux					
2. Optional material: 316 Extra, 316L Extra					
3. 3MP for optional, 20X, 30X for optional					
<b>EXPLOSION-PROOF PAN/TILT</b>					
Photo	Model	Load Type	Lens	EX level	Features
	KX-EX900PPY	Side load	NO	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof Explosion--corrosion, waterproof horizontal 360°, Vertical : +75°~90° Burden weight≤20kg AC22V/24V optional
	KX-EX901PPY	Top load	NO	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. level Explosion proof Explosion--corrosion, waterproof horizontal 360°, Vertical : ±45° Burden weight≤20kg AC22V/24V optional
1. Optional material: 316 Extra, 316L Extra					
<b>EXPLOSION-PROOF CONTROL BOX</b>					
Photo	Model	Material	Size (Inner/outer)	EX level	Features
	KX-EX08CB61-C	High-Quality carbon steel	200×250×100mm 335×280×125mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	High-Quality carbon steel C-level Explosion proof Explosion--corrosion, waterproof 6*G3/4" interface Medium anti-corrosion
	KX-EX08CB62-C	High-Quality carbon steel	400×300×150mm 485×405×165mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	
	KX-EX08CBD61	304 stainless Steel	200×250×100mm 335×280×125mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel level Explosion proof Explosion--corrosion, waterproof 6*G3/4" interface Strong anti-corrosion
	KX-EX08CBD62	304 stainless Steel	400×300×150mm 485×405×165mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	
	KX-EX08CBJ43-A	Aluminum	190*125*60mm 200*200*100mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Aluminum <b>Power box</b> B-level Explosion proof Explosion--corrosion, waterproof 4*G3/4" interface Slight anti-corrosion
	KX-EX08CBJ24-A	Aluminum	125*125*60mm 135*200*100mm	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Aluminum <b>Junction box</b> B-level Explosion proof Explosion--corrosion, waterproof 2*G3/4" interface Slight anti-corrosion
1. Optional material: 316 Extra, 316L Extra					
2. Optional: built in AC220 to AC 24V, built in AC220 to DC 12V,					
<b>EXPLOSION-PROOF IR LAMP</b>					
Photo	Model	IR Distance	EX level	Features	
	KX-EX700IR50	50M	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	304 stainless steel (316,316L for optional), apply to strong corrosive environment. B-level Explosion proof Explosion--corrosion, waterproof 850NM IR optional for DC12V/AC220 power 2*G3/4" interface for wire	
	KX-EX700IR100	100M	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db		
1. Optional material: 316 Extra, 316L Extra					
2. Optional: AC220V					



### INSTALLATION ACCESSORIES

Photo	Model	Material	EX level	Features
	KX-EX18L1000	Stainless Steel	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	3/4 interface, caliber20mm, length1000mm
	KX-EX15L1000	Stainless Steel	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	20*1.5mm interface caliber 15mm, length1000mm
	KX-EX06BS-C	High-quality carbon steel	---	Suitable for all IR bullet and explosion proof housing
	KX-EX06BS	304 stainless steel	---	
	KX-EX01BY-C	High-quality carbon steel	---	suitable for all PTZ and pan & tilt
	KX-EX01BY	304 stainless steel	---	
	KX-EX06BS-C-W	High-quality carbon steel	---	Ex-universal joint
	KX-EX06BS-W	304 stainless steel	---	
	KX-EX08CBS42-A	Aluminum	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db	Three way junction box
1. Bracket Optional material: 316Extra, 316L Extra				
1. Pipe Optional material: 304 Extra				